

Product Datasheet

Characteristic

XMLA020C2S11

pressure switch XMLA 20 bar - fixed
scale 1 threshold - 1 C/O



Main

range of product	OsiSense XM
product or component type	electromechanical pressure sensor
pressure sensor type	electromechanical pressure sensor
device short name	XMLA
pressure sensor size	290.08 psi (20 bar)
controlled fluid	corrosive fluid (32...320 °F (0...160 °C))
fluid connection type	G 1/4 (female) conforming to ISO 228
electrical connection	screw-clamps terminals 1 x 0.5...2 x 2.5 mm ²
AWG gauge	AWG 20...AWG 14
cable entry number	1 tapped entry (Pg 13.5) forcable gland , cable outer diameter: 0.35...0.51 in (9...13 mm)
contacts type and composition	1 C/O
product specific application	-
pressure switch type of operation	detection of 1 single threshold
electrical circuit type	control circuit
scale type	fixed differential
local display	with
adjustable range of switching point on rising pressure	14.5...290.08 psi (1...20 bar)
adjustable range of switching point on falling pressure	8.7...275.57 psi (0.6...19 bar)
maximum permissible accidental pressure	652.67 psi (45 bar)
destruction pressure	1305.34 psi (90 bar)
pressure actuator	diaphragm
materials in contact with fluid	PTFE 316L stainless steel
enclosure material	zinc alloy
[In] rated current	3 A, B300, AC-15 (Ue = 120 V) conforming to EN/IEC 60947-5-1 1.5 A, B300, AC-15 (Ue = 240 V) conforming to EN/IEC 60947-5-1 0.1 A, R300, DC-13 (Ue = 250 V) conforming to EN/IEC 60947-5-1

Complementary

natural differential at low setting	5.8 psi (0.4 bar) (+/- 0.2 bar)
natural differential at high setting	14.5 psi (1 bar) (+/- 0.1 bar)

maximum permissible pressure - per cycle	362.59 psi (25 bar)
terminal block type	4 terminals
operating rate	< 120 cyc/mn at > 32 °F (0 °C)
repeat accuracy	< 2 %
[Ui] rated insulation voltage	300 V conforming to UL 508 500 V conforming to EN/IEC 60947-1 300 V conforming to CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-1
auxiliary contacts operation	snap action
contacts material	silver contacts
resistance across terminals	< 25 mOhm conforming to IEC 255-7 category 3 < 25 mOhm conforming to NF C 93-050 method A
short circuit protection	10 A cartridge fuse type gG (gl)
mechanical durability	5000000 cycles
setting	external
height	4.45 in (113 mm)
depth	2.95 in (75 mm)
width	1.38 in (35 mm)
product weight	1.51 lb(US) (0.685 kg)

Environment

standards	CE EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14
product certifications	BV CCC CSA LROS (Lloyds register of shipping) UL EAC
protective treatment	TC (standard version)
ambient air temperature for operation	-13...158 °F (-25...70 °C)
ambient air temperature for storage	-40...158 °F (-40...70 °C)
operating position	any position
vibration resistance	4 gn (f = 30...500 Hz) conforming to IEC 60068-2-6
shock resistance	50 gn conforming to IEC 60068-2-27
class of protection against electric shock	class I conforming to IEC 1140 class I conforming to IEC 536 class I conforming to NF C 20-030
IP degree of protection	IP66 conforming to EN/IEC 60529

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0928 -
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------