



Main

Range of Product	Modicon Premium Automation platform
Product or Component Type	Unity processor
Software designation	Unity Pro

Complementary

Concept	Transparent Ready
Number of racks	16 4/6/8 slots 8 12 slots
Number of slots	128 96 64
Discrete I/O processor capacity	2040 I/O
Analogue I/O processor capacity	512 I/O
Number of application specific channel	64
Number of process control channel	30 up to 90 simple loops
Integrated connection type	Non isolated serial link female mini DIN RS485)19.2 kbit/s) Ethernet TCP/IP RJ45 USB port12 Mbit/s)
Port Ethernet	10BASE-T/100BASE-TX
Communication module processor capacity	1 3 8 5
Memory description	Internal RAM (with PCMCIA card) 2048 kB data Internal RAM (with PCMCIA card) 7168 kB program Internal RAM (without PCMCIA card) 2048 kB program and data PCMCIA card 16384 kB additional data storage
Maximum size of object areas	128 %MWi internal words located internal data 32768 %Mi located internal bits 64 %KW constant words located internal data Unlimited (DFB and EFB function blocks) unlocated internal data Unlimited (elementary and derived data) unlocated internal data
Application structure	1 fast task 32 timers 1 master task 4 auxiliary tasks 128 event tasks
Execution time per instruction	0.0375...0.045 µs Boolean with PCMCIA card 0.0375...0.045 µs Boolean without PCMCIA card 0.045...0.06 µs word or fixed-point arithmetic with PCMCIA card 0.045...0.06 µs word or fixed-point arithmetic without PCMCIA card 0.48...0.56 µs floating points with PCMCIA card 0.48...0.56 µs floating points without PCMCIA card
Number of instructions per ms	14 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card 14 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card 20.26 Kinst/ms 100 % Boolean with PCMCIA card 20.26 Kinst/ms 100 % Boolean without PCMCIA card

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

System overhead	0.07 Ms fast task 1 ms master task
Marking	CE
Local signalling	For Ethernet TCP/IP port ready (RUN) 1 LED (green) For processor running (RUN) 1 LED (green) For collision detection (COL) 1 LED (red) For Ethernet TCP/IP port fault (ERR) 1 LED (red) For I/O module or configuration fault (I/O) 1 LED (red) For processor or system fault (ERR) 1 LED (red) For activity on TER or AUX terminal port (TER) 1 LED (yellow) For Ethernet link diagnostics (STS) 1 LED (yellow) For reception activity (RX) 1 LED (yellow) For transmission activity (TX) 1 LED (yellow)
Current consumption	1880 mA 5 V DC
Module format	Double
Net Weight	1.34 lb(US) (0.61 kg)

Environment

Standards	CSA C22.2 No 213 Class I Division 2 Group C IEC 61131-2 UL 508 CSA C22.2 No 213 Class I Division 2 Group D CSA C22.2 No 213 Class I Division 2 Group B 73/23/EEC 93/68/EEC CSA C22.2 No 142 CSA C22.2 No 213 Class I Division 2 Group A 89/336/EEC 92/31/EEC
Product Certifications	DNV[RETURN]RINA[RETURN]LR[RETURN]GL[RETURN]BV[RETURN]RMRS[RETURN]ABS
Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Relative Humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...6561.68 ft (0...2000 m)
Protective treatment	TC
IP Degree of Protection	IP20
Pollution degree	2

Ordering and shipping details

Category	22558-TSX PREMIUM, ATRIUM & PL7 PRO
Discount Schedule	PC22
GTIN	3595863926477
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.74 in (9.5 cm)
Package 1 Width	7.09 in (18.0 cm)
Package 1 Length	10.24 in (26.0 cm)
Package 1 Weight	2.34 lb(US) (1.061 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	14.03 lb(US) (6.366 kg)

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov


Contractual warranty

Warranty

18 months

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) With screw terminal block modules.
- (2) Maximum depth for all types of modules and their associated connectors.