



## Overview

Lead time	Usually in Stock
-----------	------------------

## General

Provided equipment	User Manual
--------------------	-------------

## Physical

Cable length	10 ft (3.05 m)
Color	Black Gray
Depth	1.18 in (3 cm)
Height	11.02 in (28 cm)
Product Weight	1.48 lb(US) (0.67 kg)
Width	2.05 in (5.2 cm)

## Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Maximum Input Current per Phase	15 A
Switching current capacity	15 A
Nominal Input Voltage	120 V

## Output

Number of power socket outlets	6
Outlet standard	NEMA 5-15R

## Conformance

UL 1449 TVSS Rating	500
Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	48 KA common mode 24 kA normal mode
Surge energy rating	1080 J

## Ordering and shipping details

GTIN	00731304336600
Package weight(Lbs)	1.70 lb(US) (0.77 kg)

## Packing Units

Package 1 Height	12.20 in (31 cm)
Package 1 width	5.71 in (14.5 cm)
Package 1 Length	1.57 in (4 cm)
SCC14	10731304336607
Number of Units in Package 2	6
Package 2 Weight	10.85 lb(US) (4.92 kg)
Package 2 Height	13.58 in (344.93 mm)
Package 2 width	6.42 in (163.07 mm)
Package 2 Length	10.71 in (272.03 mm)
Number of Units in Package 3	264

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	Limited Lifetime
----------	------------------