

Copper Clad Groundrods and Connectors



CATALOGUE #	SIZE	WT./LBS./C	CATALOGUE #	SIZE	WT./LBS./C	
1205CC	1/2" x 5"	260	3406CC	3/4" x 6"	720	
1206CC	1/2" x 6"	305	3408CC	3/4" x 8"	960	
1208CC	1/2" x 8"	410	3409CC	3/4" x 9"	1080	
1210CC	1/2" x 10"	520	3410CC	3/4" x 10"	1200	
5805CC	5/8" x 5"	400	1008CC	1" x 8"	1700	
5806CC	5/8" x 6"	580	1010CC	1" x 10"	2130	
5808CC	5/8" x 8"	640				
5809CC	5/8" x 9"	740				
5810CC	5/8" x 10"	800				

Sectional Copper Clad Rods

CATALOGUE #	SIZE	WT./LBS./C	CATALOGUE #	SIZE	WT./LBS./C	
1208SC	1/2" x 8"	410	3408SC	3/4" x 8"	960	
1210SC	1/2" x 10"	510	3410SC	3/4" x 10"	1200	
5808SC	5/8" x 8"	640	1010SC	1" x 10"	2130	
5810SC	5/8" x 10"	800				

Couplings

Driving Studs

CATALOGUE #	SIZE	WT./LBS./C	CATALOGUE #	SIZE	WT./LBS./C	
12SC	1/2"	15	12DS	1/2"	15	
58SC	5/8"	26	58DS	5/8"	23	
34SC	3/4"	42	34DS	3/4"	35	
10SC	1"	85	10DS	1"	81	

Sectional copper clad rods are threaded at top and bottom. Two or more rods may be coupled together to make up the desired length. Threaded couplings are made of bronze. Driving studs are made of high strength carbon steel and are used to prevent damage to top-end threads or couplings. 1 stud required every 2 rods.