

H362AWAVW

Safety switch, heavy duty, fusible, 60A,
600VAC/DC, 3 poles, 50HP, NEMA 12K,
Appleton, view window



Main

Product	Receptacle Switch
For Use With	Plug ACP6034BC Appleton Powertite
Disconnect Type	Fusible disconnect
Phase	3 phase
Number of Poles	3
Current rating	60 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 12K
Maximum Horse Power Rating	15 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 Hp at 480 V AC 50-60 Hz for 3 phase motors 15 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 Hp at 600 V AC 50-60 Hz for 3 phase motors 10 hp at 250 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire Without neutral
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) (AWG 8) 35 lbf.in (3.95 N.m) (AWG 14...AWG 10)
Depth	7 in (177.80 mm)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)

Environment

Certifications	UL Listed
----------------	-----------

Ordering and shipping details

Category	00124-H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	785901351924
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.75 in (47.625 cm)
Package 1 Width	7.00 in (17.78 cm)
Package 1 Length	10.37 in (26.352 cm)
Package 1 Weight	17.00 lb(US) (7.711 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------