



Main

Product or component type	Communication card
Range compatibility	Altivar 71 Altivar 61
Communication port protocol	Ethernet Powerlink
Connector type	2 RJ45 connectors
Transmission rate	10/100 Mbps
Physical interface	IEEE 802.3 Ethernet Powerlink

Complementary

Number of addresses	239
Exchange mode	Half duplex
Display type	1 LED MS (Module Status) 1 LED TX/RX (Transmit/Receive port 1) 1 LED TX/RX (Transmit/Receive port 2)
Net weight	0.77 lb(US) (0.35 kg)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.82 oz (165 g)
Package 1 Height	2.36 in (6 cm)
Package 1 width	5.51 in (14 cm)
Package 1 Length	7.28 in (18.5 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	36
Package 2 Weight	15.10 lb(US) (6.848 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	144

Package 3 Weight	82.16 lb(US) (37.268 kg)
Package 3 Height	31.50 in (80 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	23.62 in (60 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration