

CHU365REI2

400A 3P Type3R 600V Heavy Duty Non-Fusible Safety Switch & Electrical Interlock



Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Non-fusible disconnect
Number of poles	3
Electrical connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	400 A
Device composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Maximum Horse Power Rating	125 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52 250 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 350 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 50 Hp 250 V DC 50 hp at 600 V DC
Height	50.31 in (1277.87 mm)
Maximum Width	27.88 in (708.15 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	550 lbf.in (62.14 N.m) AWG 1/0...750 kcmil)

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 galvanized steel

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.