PENE8, Oxide Inhibitor, 8 ounce

By Burndy
Catalog # PENE8

Oxide Inhibiting Electrical Joint Compound, 8 OZ, For Cu-Cu, Cu Conduit Threads & Grounding Applications



Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

Application

Copper to copper applications

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance Status	CM
Certification - cULus	No
EU RoHS Indicator	Yes
UL Listed	Yes
Certification - CSA Approved	No

Dimensions

Package Height	7.500 in
Package Weight	7.800 lb.
Package Length	9.000 in
Package Width	6.750 in

General

Application - For Use On	Copper to Copper
Trade Name	PENETROX™
Sub Brand	PENETROX
Container Type	Squeeze Bottle
UPC	781810592854
Type	Sealing compound
Pour Point	-40 °F
UPC 12 Digit	781810592854
UPC 14 Digit GTIN	00781810592854

Logistics

Pallet Quantity	1800
Carton Quantity	12
Container Size	8 oz

Operational

Temperature - Dropping Point Fahrenheit	350 °F
Viscosity at 100 Fahrenheit	250 °F

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved