



- ▶ Free of iron, sulfur and chlorine so as not to contaminate stainless steel
- ▶ Type 27 allows more clearance for flush cutting
- ▶ Metal hub cladding for extra strength, control and safety



**Best wheel life and extra fast cutting in aluminum and other non-ferrous alloys*



ZIP STAINLESS™

Guaranteed not to contaminate stainless steel

The new and improved Zip Stainless™ is better than ever. This cut-off wheel is free of iron, sulfur and chlorine, ensuring it will not contaminate stainless steel or other nickel alloyed steels. It offers cool, free cuts and the best overall performance on nickel alloyed steels.

TYPE 1



Dia.	Thick.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-F 042	A-60	13,300	25	400
5"	3/64" (.045")	7/8"	11-F 052	A-60	12,200	25	400
6"	3/64" (.045")	7/8"	11-F 062	A-60	10,200	25	200
7"	1/16" (.062")	7/8"	11-F 072	A-46	8,600	25	100
9"	5/64" (.078")	7/8"	11-F 092	* A-46	6,600	25	100

** Must be used with 3" clamping flange No. 30-B 022 (according to ANSI B7.1)*

TYPE 27



Dia.	Thick.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-F 142	A-60	13,300	25	200
5"	3/64" (.045")	7/8"	11-F 152	A-60	12,200	25	400
6"	3/64" (.045")	7/8"	11-F 162	A-60	10,200	25	200
7"	1/16" (.062")	7/8"	11-F 172	A-46	8,600	25	100
9"	5/64" (.078")	7/8"	11-F 192	A-46	6,600	25	100

ZIP ALU™

Fast and free cutting of aluminum without clogging

ZIP ALU™ is designed to provide long life and quick cuts on aluminum and other non-ferrous alloys. Our special abrasive blend provides smooth, cool cuts and is guaranteed not to clog, saving you time and money.

TYPE 1



Dia.	Thick.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-U 042	A-60-ZIP-ALU	13,300	25	400
5"	3/64" (.045")	7/8"	11-U 052	A-60-ZIP-ALU	12,200	25	400
6"	3/64" (.045")	7/8"	11-U 062	A-60-ZIP-ALU	10,200	25	200
7"	1/16" (.062")	7/8"	11-U 072	A-30-ZIP-ALU	8,600	25	100

TYPE 27



Dia.	Thick.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-U 142	A-60-ZIP-ALU	13,300	25	400
5"	3/64" (.045")	7/8"	11-U 152	A-60-ZIP-ALU	12,200	25	400
6"	3/64" (.045")	7/8"	11-U 162	A-60-ZIP-ALU	10,200	25	200
7"	1/16" (.062")	7/8"	11-U 172	A-30-ZIP-ALU	8,600	25	100