

SPLICE KITS

COPPER BUTT SPLICE KITS



- UL Listed
- 600 Volts maximum, 221°F (105°C) temperature rating
- Meets the requirements of the 2014 National Electric Code: Articles: 110.14(B), 300.5(E) and 300.50(D)
- Designed to simplify splicing copper conductors



PART NO.	UL LISTED WIRE RANGE OF KIT	DESCRIPTION	ORDER UNIT	UNIT QTY.	UNIT PKG.	CARTON QTY.
CSK-14-8	14 - 8 AWG Copper	Butt Splice Kit includes one (1) Copper Butt Splice Connector and one (1) 4 in. piece of Heat Shrink Tube	EA	1	BG	24
CSK-8-2	8 - 2 AWG Copper	Butt Splice Kit includes one (1) Copper Butt Splice Connector and one (1) 4 in. piece of Heat Shrink Tube	EA	1	BG	24

C

DUAL RATED BUTT SPLICE KITS – FOR DIRECT BURIAL



- For use with aluminum and copper conductors
- UL Listed
- 600 Volts maximum, 221°F (105°C) temperature rating
- Meets the requirements of the 2014 National Electric Code: Articles: 110.14(B), 300.5(E) and 300.50(D)



PART NO.	UL LISTED WIRE RANGE OF KIT	DESCRIPTION	ORDER UNIT	UNIT QTY.	UNIT PKG.	CARTON QTY.
ASK-8-4	8 - 4 AWG AL/CU	Dual Rated Butt Splice Kit includes one (1) Dual Rated Connector and two (2) Heat Shrink Tubes	EA	1	BG	24
ASK-2-1/0	2 - 1/0 AWG AL/CU	Dual Rated Butt Splice Kit includes one (1) Dual Rated Connector and two (2) Heat Shrink Tubes	EA	1	BG	24
ASK-2/0-250	2/0 - 250 MCM AL/CU	Dual Rated Butt Splice Kit includes one (1) Dual Rated Connector and two (2) Heat Shrink Tubes	EA	1	BG	24