



Main

Product Range	Type S
Component type	Auxiliary Contact Module
Used with	Contactors starter

Complementary

NEMA size	1 3 4 2 6 0 00 5 7
Auxiliary contact composition	1 NC
[Uc] control circuit voltage	<= 600 V AC 50/60 Hz
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 1.5 A 480 V AC inductive control circuit UL 508 10 A <= 600 V AC resistive control circuit UL 508

Environment

Product Certifications	UL Listed[RETURN]CSA[RETURN]UL Recognized
------------------------	---

Ordering and shipping details

Category	21761-9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	785901733812
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.50 in (3.81 cm)
Package 1 Width	3.00 in (7.62 cm)
Package 1 Length	4.50 in (11.43 cm)
Package 1 Weight	3.36 oz (95.254 g)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

China RoHS Regulation	China RoHS Declaration
-----------------------	--

Contractual warranty

Warranty	18 months
----------	-----------
