



## Overview

Lead time	Usually in Stock
-----------	------------------



## General

Provided Equipment	Installation guide Rack Mounting brackets
--------------------	--

## Physical

Cable length	12 ft (3.66 m)
Color	Black
Depth	2.24 in (5.7 cm)
Height	1.73 in (4.4 cm)
Product Weight	5.51 lb(US) (2.5 kg)
Width	17.60 in (44.7 cm)

## Input

Line Rated Current	16 A
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz
Plug standard	NEMA 5-20P
Nominal Input Voltage	100 V 120 V

## Output

Number of power socket outlets	10 NEMA 5-20R
--------------------------------	---------------

## Conformance

Product Certifications	CUL Listed UL Listed
------------------------	-------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

GTIN	00731304203889
Package weight(Lbs)	8.02 lb(US) (3.64 kg)

## Packing Units

Package 1 Height	2.76 in (7 cm)
Package 1 width	18.27 in (46.4 cm)
Package 1 Length	9.02 in (22.9 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------