

## 24-Hour Mechanical Time Switch in Enclosure

### T100 Series

Heavy-duty mechanical time switches control a single load

#### Applications

- Pumps • Lighting • Heaters

#### Features

- Highest motor load ratings in the industry
- 12 ON/OFF operations per day
- One ON and one OFF tripper included
- Available with pool heater protection
- Teeter-type terminals for multiple load connections



T104P3



T101R201



Model #	Switch	Input Voltage	Enclosure
<b>Without Pool Heater Protection</b>			
T101P3	SPST	120 VAC, 60 Hz	Outdoor Type 3R Plastic
T104P3	DPST	208-277 VAC, 60 Hz	
T106P3	1 NO/1 NC	208-277 VAC, 60 Hz	
T101R3	SPST	120 VAC, 60 Hz	Outdoor Type 3R Metal
T104R3	DPST	208-277 VAC, 60 Hz	
<b>With Pool Heater Protection</b>			
T101P201	SPST	120 VAC, 60 Hz	Outdoor Type 3R Plastic
T104P201	DPST	208-277 VAC, 60 Hz	
T101R201	SPST	120 VAC, 60 Hz	Outdoor Type 3R Metal
T104R201	DPST	208-277 VAC, 60 Hz	

#### Accessories/Replacements

Extra/replacement trippers 1 ON and 1 OFF	156T1978A
Replacement 125 VAC, 60 Hz Motor (T101P3, T101R3, T101P201, T101R201)	WG1570
Replacement 208-277 VAC, 60 Hz Motor (T104P3, T106P3, T104R3, T104P201, T104R201)	WG1573
Insulator	124--00066

Ratings	
<b>Heater Control Circuit</b>	10 A, 250 VAC MAX, 60 Hz
<b>Resistive</b>	40 A @ Varying Voltages, 60 Hz
<b>Inductive Ballast</b>	40 A @ Varying Voltages, 60 Hz
<b>Electronic Ballast</b>	16 A, 277 VAC, 60 Hz
<b>Tungsten</b>	40 A @ Varying Voltages, 60 Hz
<b>Pilot Duty</b>	1000 VA @ Varying Voltages, 60 Hz
<b>Motor</b>	2 HP, 24 FLA @ 120 VAC, 60 Hz, 5 HP, 28 FLA @ 240 VAC, 60 Hz
<b>Max Power Consumption</b>	3 W
<b>Operating Temperature</b>	-40° F to 130° F (-40° C to 54° C)
<b>Enclosure Dimensions</b>	
<b>H x W x D</b>	
<b>Plastic Outdoor</b>	10" x 6.5" x 4" (254 mm x 165.1 mm x 101.6 mm)
<b>Metal Indoor</b>	10.125" x 6.5" x 3.625" (257.2 mm x 165.1 mm x 92.1 mm)
<b>Knockout Dimensions</b>	
<b>Side/Back</b>	½" and ¾" combination
<b>Bottom</b>	(2) ½" and ¾"
<b>Warranty</b>	1-year

### Voltage Ratings

For more details on model numbers/voltage ratings scan the QR code with your smartphone or tablet.

