



## Main

Type	TF
------	----

## Complementary

Power Rating	500 VA UL 500 VA CSA 500 VA NOM 300 VA CE
Primary to Secondary Voltage	600 V 120 V 575 V 115 V 550 V 110 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Height	5.1 in (129.54 mm)
Width	4.5 in (114.30 mm)
Depth	5.46 in (138.68 mm)
Material	Copper: winding

## Environment

Product Certifications	CE[RETURN]CSA file LR37055 guide 184-N-90[RETURN]JUL listed file E61239
Insulation temperature	356 °F (180 °C)

## Ordering and shipping details

Category	16203-9070 TF (NOT T) 250-1000VA
Discount Schedule	CP8
GTIN	785901039266
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.50 in (16.51 cm)
Package 1 Width	6.70 in (17.018 cm)
Package 1 Length	7.50 in (19.05 cm)
Package 1 Weight	12.83 lb(US) (5.82 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------