

Product data sheet

Characteristics

8903SQG2V04

Contacteur, Type S, multipole lighting, electrically held, 100A, 3 pole, 277 VAC 60 Hz coil, NEMA 1



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	277 V AC 60 Hz
Current Rating	100 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	25.16 in (639 mm)
Depth	8.98 in (228 mm)
Maximum Width	11.26 in (286 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S°C) ELECT.
Discount Schedule	CP1
GTIN	00785901625933
Nbr. of units in pkg.	1
Package weight(Lbs)	33.44 lb(US) (15.17 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	11.00 in (27.940 cm)
Package 1 width	11.80 in (29.972 cm)
Package 1 Length	25.60 in (65.024 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------