

# HU362AWAVW

Safety switch, heavy duty, non fusible, 60A, 600VAC/DC, 3 poles, 60HP, NEMA 12K, Appleton receptacle, viewing window



## Main

Product	Receptacle Switch
For Use With	Plug ACP6034BC Appleton Powertite
Disconnect Type	Non-fusible disconnect
Phase	3 phase
Number of Poles	3
Current rating	60 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 12K
Maximum Horse Power Rating	50 Hp at 480 V AC 50-60 Hz for 3 phase motors 60 Hp at 600 V AC 50-60 Hz for 3 phase motors 10 hp at 250 V DC

## Complementary

Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire Without neutral
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) (AWG 8) 35 lbf.in (3.95 N.m) (AWG 14...AWG 10)
Depth	7 in (177.80 mm)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)

## Environment

Certifications	UL Listed
----------------	-----------

## Ordering and shipping details

Category	00124-H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	785901351955
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.75 in (47.625 cm)
Package 1 Width	7.00 in (17.78 cm)
Package 1 Length	10.37 in (26.352 cm)
Package 1 Weight	12.00 lb(US) (5.443 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------