
BURNDY

GB29, Mechanical Grounding Connector, Cable to Bar



By Burndy
Catalog # GB29

Mechanical Grounding Connector, Cable to 1/4" Thick Bar, 2/0 AWG (Sol) -250 kcmil, 1/2" Stud, 2 IN Width

Features

- High copper alloy ground connector for joining a range of cable to 1/4" thick bar
- Type GB separates cable from bar
- Silicon Bronze Hardware
- Rated for Direct Burial in earth or concrete
- UL467

Application

For Copper Cable To Bar, Direct Burial Cable

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - Copper Str Size	• 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil
Conductor - Copper Solid Size	• 2/0 AWG • 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Size Range	2/0 AWG - 250 kcmil
Conductor - Copper Str Size Range	2/0 AWG - 250 kcmil

Dimensions

Package Height	0.000 in
Dimension - Height mm	58.9 mm
Dimension - Height inch	2.32 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	32 mm
Dimension - Width fraction	1-7/8 in
Dimension - Width inch	1.88 in
Dimension - B Length inch	1.25 in
Dimension - Length Overall inch	1.25 in

Force Related

Installation Torque Recommended in-lb	480 lb-in

General

Product Family	Grounding and Bonding Connectors>Copper Mechanical Grounding Connectors>Cable(s) to Bar/Flat
Material Type - Screw	DURIUM™ Silicon Bronze
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	No
Sub Brand	MECHANICAL CONNECTOR
Product Type	Mechanical
UPC	781810231272
Type	GB
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810231272
UPC 14 Digit GTIN	00781810231272

Logistics

Pallet Quantity	2400
Carton Quantity	12

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved