

Product Datasheet

Characteristic

XMLG100D23

pressure sensor XMLG - 0..100 bar -
1/4" NPT male- 24V- 4..20mA



Main

range of product	OsiSense XM
product or component type	Electronic pressure sensors
pressure sensor type	Pressure transmitter
pressure sensor name	XMLG
pressure sensor size	1450.38 psi (100 bar)
fluid connection type	1/4" - 18 NPT (male)
controlled fluid	Fresh water (0...125 °C) Air (5...257 °F (-15...125 °C)) Corrosive fluid (5...257 °F (-15...125 °C)) Hydraulic oil (5...257 °F (-15...125 °C))
type of output signal	Analogue
analogue output function	4...20 mA, 2 wires
electrical connection	3 pins 1 male connector M12
[Us] rated supply voltage	12 V DC, voltage limits: 8...33 V 24 V DC, voltage limits: 8...33 V
quantity per set	Set of 1
type of packing	Individual
diameter	0.9 in (22.8 mm)

Complementary

pressure setting range	0...1450.38 psi (0...100 bar)
maximum permissible accidental pressure	3263.35 psi (225 bar)
destruction pressure	3625.94 psi (250 bar)
local display	Without
electrical circuit type	Control circuit
current consumption	< 20 mA
materials in contact with fluid	FPM (Viton) Ceramic Stainless steel type AISI 303 PPS
operating position	Any position
protection type	Load short-circuit Reverse polarity
surge withstand	1 kV (42 Ohm) conforming to EN/IEC 61000-4-5 500 kV (12 Ohm) conforming to EN/IEC 61000-4-5
[Uimp] rated impulse withstand voltage	0.5 kV

response time on output	< 2 ms
drift of the sensitivity	+/- 0.015 % of measuring range/°C
drift of the zero point	+/- 0.015 % of measuring range/°C
measurement accuracy	+/- 0.3 % of the measuring range
repeat accuracy	+/- 0.1 % of the measuring range
mechanical durability	>= 10000000 cycles
product weight	0.21 lb(US) (0.095 kg)
height	58.1 mm
length	1.91 in (48.5 mm)

Environment

standards	CE EN/IEC 61326-2-3
product certifications	EAC UL 508 CSA C22.2 No 14
protective treatment	TC
ambient air temperature for operation	5...185 °F (-15...85 °C)
ambient air temperature for storage	-40...185 °F (-40...85 °C)
vibration resistance	20 gn (f = 9...2000 Hz) conforming to EN/IEC 60028-2-6
shock resistance	25 gn 11 ms conforming to EN/IEC 60068-2-27
resistance to electrostatic discharge	15 kV (in air) conforming to EN/IEC 61000-4-2 8 kV (on contact) conforming to EN/IEC 61000-4-2
resistance to electromagnetic fields	182.88 V/yd (200 V/m) (80...1000 Hz) conforming to EN/IEC 61000-4-3
resistance to fast transients	4 kV conforming to EN/IEC 61000-4-4
resistance to conducted disturbances	30 V (0.15...80 Hz) conforming to EN/IEC 61000-4-6
resistance to magnetic fields	9.14 A/ft (30 A/m)
IP degree of protection	IP66 conforming to EN/IEC 60529 IP67 conforming to EN/IEC 60529
NEMA degree of protection	NEMA 4

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold