Product data sheet
Characteristics

XZCP1264L15
Con. M12 - Female - 90° - 5 pins - 15m pre-wired

Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors

Complementary

Electrical connection	Elbowed female connector M12, 5 pins (included earth pin)
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	49.21 ft (15 m)
Cable outer diameter	0.23 in (5.9 mm)
Cable composition	5 x 0.34 mm²
Wire insulation material	PUR
[Ue] rated operational voltage	30 V AC 36 V DC
[In] rated current	4 A
Contact resistance	5000 µOhm
Minimum insulating resistance	1 GΩ

Environment

IP degree of protection	IP65 IP69K IP67
Product certifications	CULus
Ambient air temperature for operation	-40…176 °F (-40…80 °C) static 23…176 °F (-5…80 °C) flexing
Ambient air temperature for storage	-40…176 °F (-40…80 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	18.34 oz (520 g)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	2.05 in (5.2 cm)
Package 1 width	7.32 in (18.6 cm)
Package 1 Length	8.03 in (20.4 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	7
Package 2 Weight	9.27 lb(US) (4.207 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes