



### Main

range	TeSys
product name	TeSys LRF
device short name	LR9F
product or component type	Electronic thermal overload relay
relay application	Motor protection
product compatibility	LC1F115...LC1F185
network type	AC
thermal overload class	Class 10 IEC 60947-4
thermal protection adjustment range	60...100 A

### Complementary

network frequency	50/60 Hz
supply voltage limits	17...32 V
mounting support	Direct on contactor Plate
tripping threshold	1.12 +/- 0.06 I <sub>n</sub> tripping IEC 60947-4-1
surge withstand	4 kV IEC 61000-4-5
contacts type and composition	1 NO + 1 NC
[I <sub>th</sub> ] conventional free air thermal current	5 A control circuit
[U <sub>e</sub> ] rated operational voltage	1000 V AC 50/60 Hz power circuit VDE 0110 group C
[U <sub>i</sub> ] rated insulation voltage	Power circuit 1000 V AC IEC 60947-4
[U <sub>imp</sub> ] rated impulse withstand voltage	IEC 60947-1 8 kV
phase failure sensitivity	Tripping in 4 s +/- 20 % IEC 60947-4-1
reset	Manual reset on front relay
control type	Dial White full-load current adjustment Test button Red Push-button Red reset Push-button stop
local signalling	Trip indicator
temperature compensation	-4...158 °F (-20...70 °C)
current consumption	<= 5 mA no-load
switching capacity in mA	0...150 mA

maximum voltage drop	<2.5 V closed state
connections - terminals	Control circuit screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) flexible - with cable end Control circuit screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) solid Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (0.75...4 mm <sup>2</sup> ) flexible - without cable end Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...1.5 mm <sup>2</sup> ) flexible - with cable end Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible - without cable end Control circuit screw clamp terminals 2 0.00 in <sup>2</sup> (1 mm <sup>2</sup> ) solid Power circuit lugs-ring terminals M8
tightening torque	Control circuit 1.2 N.m screw clamp terminals Power circuit 18 N.m screw clamp terminals
Maximum Height	3.78 in (96 mm)
Maximum Width	4.53 in (115 mm)
Maximum Depth	4.86 in (123.5 mm)
Net Weight	1.98 lb(US) (0.9 kg)

## Environment

standards	IEC 60255-8 VDE 0660 IEC 60255-17 IEC 60947-4-1 EN 60947-4-1
product certifications	UL CSA
protective treatment	TH
IP degree of protection	IP20 IEC 60529 IP20 VDE 0106
ambient air temperature for operation	-4...131 °F (-20...55 °C) IEC 60255-8
ambient air temperature for storage	-40...185 °F (-40...85 °C)
operating altitude	<= 6561.68 ft (2000 m) without derating
fire resistance	1562 °F (850 °C) IEC 60695-2-1
mechanical robustness	Shocks 13 Gn for 11 ms IEC 60068-2-7 Vibrations 5...300 Hz 2 Gn IEC 60068-2-6
dielectric strength	6 kV 50 Hz IEC 255-5
electromagnetic compatibility	Resistance to electrostatic discharge 6 kV in indirect mode IEC 61000-4-2 Resistance to electrostatic discharge 8 kV in air IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test 10 V/m IEC 61000-4-3 Fast transients immunity test 2 kV IEC 61000-4-4

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	ENVPEP080207EN
Circularity Profile	ENVEOLI100406
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.