



Main

Range	Multi9
Product or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	12

Complementary

Number of ways	3 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	2.13 in (54 mm)
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	115 A 104 °F (40 °C)
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz UL 508
Mounting location	Top tunnel type terminals
9 mm pitches	24
Width	8.50 in (216 mm)
Color	Light gray RAL 7035)
Range compatibility	Multi9 Multi9 C60BP

Environment

Standards	UL 508
Fire resistance	1760 °F (960 °C) 30 s) IEC 60695-2-1
Pollution degree	3
IP degree of protection	IP20 with end-pieces and tooth covers

Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192844
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.000 cm)
Package 1 Width	2.17 in (5.500 cm)
Package 1 Length	8.27 in (21.000 cm)
Package 1 Weight	5.89 oz (167.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	19.24 lb(US) (8.729 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.