

Product data sheet

Characteristics

NB15

Circuit breaker, Stab-Lok, 15A, 1 pole,
120/240VAC, 10kA, bolt on mount



Main

Range of Product	Stab-lok
Product or Component Type	Miniature circuit-breaker

Complementary

Line Rated Current	15 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Bolt-on
Poles description	1P
Breaking capacity	10 kA
Electrical Connection	Screw connector
AWG gauge	AWG 14...AWG 2 aluminium/copper

Environment

Product Certifications	CSA
------------------------	-----

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.00 in (2.54 cm)
Package 1 Width	3.00 in (7.62 cm)
Package 1 Length	3.50 in (8.89 cm)
Package 1 Weight	4.96 oz (140.614 g)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.