



Main

Product	Double Throw Safety Switch
Duty Rating	General duty
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Number of Poles	4
Current Rating	400 A
Voltage Rating	600 V AC 600 V DC
Enclosure Rating	NEMA 1
Motor power hp	125 Hp at 240 V AC 50-60 Hz for 3 phase motors 250 Hp at 480 V AC 50-60 Hz for 3 phase motors 350 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 hp at 250 V DC

Complementary

Short-circuit current	10 KA H or K 100 kA R, J or T
Fuse type	H or K R, J or T
Mounting Type	Surface
Wire Size	AWG 1/0...750 kcmil aluminium/copper
Tightening torque	550 Lbf.in (62.14 N.m) 0.08...0.47 in ² (53.49...304 mm ²) (AWG 1/0...750 kcmil) 62.14 lbf.in (7.02 N.m) 0.08...0.24 in ² (53.49...152 mm ²) (2 x AWG 1/0...2 x 300 kcmil)
Depth	8.88 in (225.55 mm)
Width	28.40 in (721.36 mm)
Height	64.20 in (1630.68 mm)
Net Weight	220.46 lb(US) (100 kg)

Environment

Certifications	UL Listed
----------------	-----------

Ordering and shipping details

Category	00033-DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	3606481716798
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.00 in (43.18 cm)
Package 1 Width	36.00 in (91.44 cm)
Package 1 Length	66.00 in (167.64 cm)
Package 1 Weight	248.00 lb(US) (112.49 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations