



Main

Product Type	Enclosure
Range of Product	QO
Load Center Type	Main lugs

Complementary

Current Rating	100 A
Interrupt Rating	22 kA
Number of Spaces	3
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QO 3P
Product Certifications	UL Listed[RETURN]CSA
Electrical Connection	Lugs
Surface Finish	Baked enamel Gray
Busbar Material	Tin plated copper
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Tightening Torque	35 lb.in, AWG 14...AWG 10, copper 35 lb.in, AWG 12...AWG 10, aluminium Main lugs 40 lb.in, AWG 8...AWG 4, aluminium/copper Main lugs 50 lb.in, AWG 3...AWG 2, aluminium/copper Main lugs 35 lb.in, AWG 14...AWG 10, copper Main lugs 35 lb.in, AWG 12...AWG 10, aluminium
Box Number	10R
Cover Type	Surface cover
Ground Bar	Grounding bar (ordered separately)
Enclosure Material	Welded galvanized steel
Enclosure Type	Enclosure
Height	13.19 in (335 mm)
Width	6.93 in (176 mm)
Depth	4.12 in (104.65 mm)

Ordering and shipping details

Category	00023-QO,Q2L 3P ENCL & BREAKERS
Discount Schedule	DE2
GTIN	785901051770
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	8.11 in (20.6 cm)
Package 1 Length	14.49 in (36.8 cm)
Package 1 Weight	8.09 lb(US) (3.67 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------