

Main

| | |
|------------------------------|---|
| Action | Standard Action |
| Actuator Type | Diaphragm |
| Application | Control electrically driven water pumps and air compressors |
| Approvals | UL Listed File: E12158 CCN NKPZ - CSA Certified File: LR25490 |
| Contact Arrangement | DPST |
| Depth | 3.68 Inches |
| Diaphragm | Nitrile (Buna N) |
| Differential | 20 to 40 PSIG |
| Differential Type | Adjustable |
| Enclosure Rating | NEMA 1 |
| Enclosure Type | General Purpose (Indoor) |
| Flange Material | Zinc Plated Steel |
| Height | 5.72 Inches |
| Horsepower Rating (1-Phase) | 2HP@115VAC - 3HP@230VAC - 5HP@460/575VAC |
| Horsepower Rating (3-Phase) | 3HP@115VAC - 5HP@230VAC - 5HP@460/575VAC |
| Includes | Two-Way pressure release valve |
| Marketing Trade Name | Pumptrol |
| Maximum Allowable Pressure | 300 PSIG |
| Maximum Voltage Rating | 575VAC |
| Mounting Type | Bracket |
| Number of Poles | 2-Pole |
| Pressure Connection | 0.25 Inch NPSF |
| Pressure Setting | 80 to 100 PSIG |
| Range on Decreasing Pressure | 40 to 170 PSIG |
| Range on Increasing Pressure | 65 to 200 PSIG |
| Terminal Type | Screw Clamp |
| Type | G |
| Weight | 2.25 Pounds |
| Width | 3.44 Inches |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.