YAL6CT14, Cu Compression, 1-Hole, 1/4" Stud, Standard Barrel, 6 AWG



By Burndy
Catalog # YAL6CT14

Copper Compression Terminal

Application

Wire Termination

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance Status	CM
Certification - cULus	No
EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	UL 486A-486B
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - Copper DLO Size Range	N/A
Conductor Size	6 AWG
Conductor - Material	COPPER
Conductor Type	CODE
Conductor - Copper Str Size Range	6 AWG
Conductor - Copper Str Size	6 AWG

Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

Current

Voltage Rating	35 kV
Voltage - Maximum	35000

Dimensions

Dimension - Pad Width inch	0.45 in
Dimension - Bolt Hole Size inch	0.27 in
Package Height	0.000 in
Dimension - Hole Size fraction	1/4
Dimension - Bolt Size fraction	1/4
Physical Attribute - Tongue Angle	Straight
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - Z inch	0.33 in
Dimension - L Length Overall mm	37 mm
Dimension - B Length inch	0.54 in
Dimension - Outside Diameter inch	0.29 in
Dimension - D inch	0.64 in
Dimension - N inch	0.31 in
Dimension - Hole Size mm	6.9 mm
Dimension - Bolt Size inch	0.25
Dimension - Hole Size inch	0.27
Dimension - Length Overall inch	1.45 in
Dimension - Stud Size inch	1/4
Dimension - Stud Size fraction	1/4

General

Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Plated	Y
Color Code	Blue
Trade Name	HYLUG™
Die Index	7
UPC	781810417584
Type	Standard Barrel, Tin Plated
Construction Material - Main	Copper
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Electro Tin plated
UPC 14 Digit GTIN	00781810417584

Operational

Temperature Rating	194

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved