



Main

Range of Product	PowerPact P
Product or Component Type	Mechanical lug
Accessory / separate part category	Connection accessory
Quantity per Set	Set of 3
Circuit breaker type	P-frame

Complementary

Product compatibility	PowerPact P PowerPact
Line Rated Current	1200 A
Material	Aluminium
Mounting Mode	Unit mount
Location of connection	Upstream Downstream
AWG gauge	AWG 3/0...600 kcmil aluminium/copper
Kcmil size	600 kcmil
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.47 in ² (95...300 mm ²) (AWG 3/0...600 kcmil)

Environment

Product Certifications	UL[RETURN]CSA
------------------------	---------------

Ordering and shipping details

Category	01250-M,P,R FRAME ACCESSORIES ONLY
Discount Schedule	DE2
GTIN	785901654728
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.50 in (13.97 cm)
Package 1 Width	7.50 in (19.05 cm)
Package 1 Length	11.50 in (29.21 cm)
Package 1 Weight	6.00 lb(US) (2.722 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------