



Main

Range of Product	Stab-lok
Product or Component Type	Miniature circuit-breaker
Line Rated Current	25 A
[Ue] rated operational voltage	120 V AC
Poles description	1P
Breaking capacity	10 kA

Complementary

Mounting Mode	Plug-in
Electrical Connection	Screw terminal
AWG gauge	AWG 14...AWG 6 aluminium/copper

Environment

Product Certifications	CSA
------------------------	-----

Ordering and shipping details

Category	39997-CANADIAN PRODUCTS
Discount Schedule	NET
GTIN	047569389030
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.00 in (7.62 cm)
Package 1 Width	0.50 in (1.27 cm)
Package 1 Length	3.40 in (8.636 cm)
Package 1 Weight	3.04 oz (86.183 g)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.