

Date: \_\_\_\_\_  
 In hands date of project: \_\_\_\_\_  
 Project name/Number: \_\_\_\_\_  
 Name of distributor: \_\_\_\_\_  
 Client #: \_\_\_\_\_  
 Name of end user: \_\_\_\_\_

## ORDERING INFORMATION

Order code: 66158  
 Description: LED/T8/14W/840/48/BYP/120-277/ND/STD  
 UPC: 69549661585  
 Case quantity: 25

## PERFORMANCE DATA

Shape: T8  
 Base: G13  
 Install method: Ballast bypass  
 Watts (W): 14  
 Lamp voltage (VAC): 120 V - 277 V  
 Color temperature (K)\*\*: 4 000  
 Initial Lumens (lm)\*: 1 800  
 Initial lumens per watt (lm/W): 129  
 Average life (L70 hours): 50 000  
 CRI: 82  
 Dimmable: No  
 Operating temperature range: -20°C / -4°F to 45°C / 113°F

\*Initial lumens range: +/- 10 %    \*\*Typical colour temperature range: +/- 5 %



MOL: 47 3/4 in. (1 213.6 mm)    Dia.: 1 in. (26 mm)



\*This product complies with UL1598C Standard for LED luminaire Retrofit kits.

## CAUTIONS

Only for ballast bypass installation in 120-277V applications. Not for use in 347V direct line voltage applications.  
 Direct replacement for 25, 28, 30 & 32 watts T8 lamps only. Do not use with dimmers. Not for emergency lighting. Risk of electric shock – for use in damp locations.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: \_\_\_\_\_

Company: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.  
 Data is based upon tests performed in a controlled environment and representative of relative performance.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.