

# Product data sheet

## Characteristics

# 8903LXG1200V03

Contactor, Type L, multipole lighting, mechanically held, 30A, 12 pole, 600 V, 220/240 VAC 50/60 Hz coil, NEMA 1



### Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or Component Type | Mechanically Held Lighting Contactor |
| Range of Product          | 8903LX                               |
| Control Circuit           | Separate control circuit             |

### Complementary

|                       |  |
|-----------------------|--|
| Control Voltage       | 220 V AC 50 Hz<br>240 V AC 60 Hz               |
| Inrush power in VA    | 180 VA 60 Hz<br>170 VA 50 Hz<br>25 VA 50/60 Hz |
| Current Rating        | 20 A tungsten<br>30 A fluorescent              |
| Number of Poles       | 12P 12 NO                                      |
| Control Unit          | No control units                               |
| Pilot Light           | No indicator                                   |
| Other Options         | None   |
| Electrical Connection | Screw-clamp terminals                          |
| Height                | 12.68 in (322 mm)                              |
| Depth                 | 6.02 in (153 mm)                               |
| Width                 | 7.80 in (198 mm)                               |

### Environment

|                        |                                    |
|------------------------|------------------------------------|
| Enclosure Type         | NEMA 1 painted sheet steel surface |
| Product Certifications | UL Listed[RETURN]CSA               |

### Ordering and shipping details

|                   |                         |
|-------------------|-------------------------|
| Category          | 21322 - 8903 LX (NOT L) |
| Discount Schedule | CP1                     |
| Returnability     | No                      |
| Country of origin | MX                      |

### Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 7.50 in (19.05 cm)     |
| Package 1 Width              | 8.00 in (20.32 cm)     |
| Package 1 Length             | 13.50 in (34.29 cm)    |
| Package 1 Weight             | 5.90 lb(US) (2.676 kg) |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product  |
| California proposition 65   | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation            | <a href="#">REACH Declaration</a>                              |
| REACH free of SVHC          | Yes  |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>                  |
| Toxic heavy metal free      | Yes  |
| Mercury free                | Yes  |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                         |
| RoHS exemption information  | <a href="#">Yes</a>  |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                  |
| Circularity Profile         | No need of specific recycling operations                       |
| PVC free                    | Yes  |
| Halogen content performance | Halogen free plastic parts product                             |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|