

CHU365AWKEI2

Safety switch, heavy duty, non fusible, 400A, 600 VAC/VDC, 3 poles, 350 hp, NEMA 12, interlock 2NO/NC



Main

Range of product	Square D
Product or component type	Single Throw Safety Switch
Line Rated Current	400 A
NEMA degree of protection	NEMA 3R/12 galvanized steel
Maximum Horse Power Rating	125 Hp at 240 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 250 Hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 350 Hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 50 Hp at 250 V DC 50 hp 600 V DC
Disconnecter device type	Non-fusible disconnect
Maximum short-circuit current	10 kA
Device mounting	Surface
Number of poles	3
Phase	3 phase
Product certifications	CSA
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Wiring configuration	4-wire

Complementary

Width	26.25 in (666.75 mm)
Height	46.25 in (1174.75 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	62.14 N.m (AWG 1/0...750 kcmil)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.