MELTRIC
A COMPANY OF MARECHAL ELECTRIC



DS60 RECEPTACLE

33-64043-352-843

SPECIFICATIONS

60 A
480 VAC
Type 4X & IP69
25 hp

Rated Current (A)	60 A
Rated Voltage (V)	480 VAC
Horsepower Rating	25 hp
Contact Configuration	3P+G
Auxiliary Contacts	NO AUX
Ratings Information	CURRENT INTERRUPTING
Environmental Rating	Type 4X IP 66/67 IP 69
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Metal Type	
Product Color	BLUE
Thread Size	
Cable Range	
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	10 AWG – 2 AWG SCREW TERMINAL
Hazardous Ratings	
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	STRAIGHT INSERTION
Option(2)	PADLOCK PAWL
Option(3)	
Option(4)	
Accessory Size	4

Base Drawing Number	33-64xxx.PDF
Catalog	meltric-catalog-ds60-en.pdf