

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens (lm)	Case qty
A21									
MOL : 5 ⁷ / ₁₆ in. (135 mm) LCL : 3 ⁷ / ₃₂ in. (90 mm)									
50075	50A21/F/2M/47V/STD	50	E26	47	Frost	2000	C-6	650	120
50076	50A21/F/2M/60V/STD	50	E26	60	Frost	2000	C-6	650	120
R20									
MOL : 3 ²⁹ / ₃₂ in. (99 mm) LCL : 2 ²⁵ / ₃₂ in. (75 mm)									
50223	17R20/F/2M/6.3V/STD	17	E26	6.3	Frost	2000	C-6	145	10
S11									
MOL : 2 ⁷ / ₁₆ in. (59 mm) LCL : 1 ¹ / ₂ in. (38 mm)									
50790	15S11/CL/1M/BA15d/75V/STD	15	BA15d	75	Clear	1 000	C-7A	140	500
50791	30S11/CL/BA15d/75V/STD	30	BA15d	75	Clear	1 000	C-7A	280	500
50792	30S11/CL/BA15d/32V/STD	30	BA15d	32	Clear	1 000	C-7A	320	500
S14									
MOL : 3 ¹ / ₁₆ in. (84 mm) LCL : 2 ⁷ / ₃₂ in. (64 mm)									
52210	11S14/CL/1.5M/6V/STD	11	E26	6	Clear	1 500	C-6	78	500
52208	11S14/CL/1.5M/12V/STD	11	E26	12	Clear	1 500	C-6	76	500
52209	11S14/CL/1.5M/24V/STD	11	E26	24	Clear	1 500	C-6	74	500

HIGH VOLTAGE LAMPS are available for specialized needs. These lamps are most commonly used in machinery as well as equipment coming from overseas.



Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens (lm)	Case qty
A15									
MOL : 3 ¹ / ₂ in. (89 mm) LCL : 2 ³ / ₈ in. (60 mm)									
14797	40A15/IF/250V	40	E26	250	Frost	5 000	C-9	300	50
A19									
MOL : 4 ¹ / ₄ in. (108 mm) LCL : 3 ¹ / ₈ in. (79 mm)									
14653	25A19/F/2M/B22/230 250V	25	B22	230	Frost	2 000	CC-9	205	100
59541	40A19/F/1M/E27/230 240V/STD	40	E27	240	Frost	1 000	CC-9	410	100
14654	40A19/F/2M/B22/230 250V	40	B22	230	Frost	2 000	CC-9	300	100
52014	50A19IFRS/230-250V/CERAMIC RED	50	E26	230	Ceramic red	2 000	C-9	N/A	120
52021	50A19/F/2M/E27/230 250V/STD	50	E27	230	Frost	2 000	CC-9	485	120
14656	100A19F/2M/B22/230 250V	100	B22	230	Frost	2 000	CC-9	1 380	100
B10									
MOL : 3 ²⁹ / ₃₂ in. (99 mm) LCL : 2 ⁷ / ₁₆ in. (65 mm)									
52158	25B10/CL/3M/E12/220V/STD	25	E12	220	Clear	3 000	C-7A	185	500
50646	40B10/CL/3M/E12/220V/STD	40	E12	220	Clear	3 000	C-7A	325	500
14446	60B10/CL/3M/E12/220V	60	E12	220	Clear	3 000	C-7A	650	500
PS35									
MOL : 9 ¹ / ₃₂ in. (239 mm) LCL : 7 in. (178 mm)									
14660	500PS35/CL/2M/E39/240V	500	E39	230	Clear	2 000	CC-9	8 500	12
T7									
MOL : 2 ⁷ / ₁₆ in. (59 mm) LCL : 1 ¹⁹ / ₃₂ in. (37 mm)									
52193	15T7/CL/1.5M/E12/250V/STD	15	E12	250	Clear	1 500	C-7A	95	1 000
52238	15T7/CL/1.5M/E17/240V/STD	15	E17	240	Clear	1 500	C-7A	95	1 000

High and Low Voltage Lamps