



Main

Accessory / separate part type	Cable
--------------------------------	-------

Complementary

Accessory / separate part designation	Bare cable
Accessory / separate part category	Cabling accessories
Cable length	82.02 ft (25 m)
Material	PvR (PVC/NBR) sheath
Colour	Matt black
Cable cross section	0.00 in ² (0.5 mm ²)
Total number of wires	4
Wire insulation material	PVC
Flame retardance	Class C2 conforming to NF C 32-070
[Ue] rated operational voltage	300 V
[Ui] rated insulation voltage	2000 V conforming to NF C 32-201-1
Bending radius	Minimum 3 x external diameter
Tensile strength	10...35 N/mm ²
Hardness	70 shores A (tolerance: +/-5)
Net weight	2.46 lb(US) (1.115 kg)

Environment

Ambient air temperature for operation	-31...194 °F (-35...90 °C)
Ambient air temperature for storage	-40...212 °F (-40...100 °C)
Environmental characteristic	Soluble resistant at 90 °C Without un moulding agent Without silicone Synthetic oils at 90 °C Mineral resistant at 90 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	2.50 lb(US) (1.133 kg)
Package 1 Height	1.18 in (3 cm)
Package 1 width	9.45 in (24 cm)
Package 1 Length	9.84 in (25 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	20.86 lb(US) (9.464 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------