



Main

Range	Multi9
Product or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	12

Complementary

Number of ways	12 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	0.71 in (18 mm)
Marking	L
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	277 V AC Ph/N 480 V AC Ph/Ph
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	12 kV
Mounting location	Top tunnel type terminals
9 mm pitches	24
Width	8.50 in (216 mm)
Color	Light gray RAL 7035)
Range compatibility	Multi9 Multi9 C60SP

Environment

Standards	IEC 60947-2 GB 14048.2 UL 1077
Fire resistance	1760 °F (960 °C) 30 s)

Ordering and shipping details

Category	00908-C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	3303430102854
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	2.17 in (5.5 cm)
Package 1 Length	8.46 in (21.5 cm)
Package 1 Weight	2.79 oz (79.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	72
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	13.10 lb(US) (5.941 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------