

Product data sheet

Characteristics

QO320ML1RB

Load center, QO, 3 phase, 20 spaces, 20 circuits, 125A convertible main lugs, NEMA3R, CSA, UL



Main

Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Cover Type	Surface cover

Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 4...AWG 2/0, aluminium/copper
PoN Convertible Mains (lugs)	Main lugs
Rated Current	125 A
Number of Spaces	20
Maximum Number of Single Pole Circuits	40
Number of Phases	3 phase
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Wiring Configuration	4-wire
Enclosure Material	Welded galvanized steel
Height	22.70 in (576.58 mm)
Width	14.72 in (373.89 mm)
Depth	4.54 in (115.32 mm)

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	cULus

Ordering and shipping details

Category	00158-CANADIAN 3-PH LOAD CENTERS
Discount Schedule	DE3
GTIN	785901751083
Returnability	Yes
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.10 in (12.954 cm)
Package 1 Width	15.40 in (39.116 cm)
Package 1 Length	23.70 in (60.198 cm)
Package 1 Weight	25.12 lb(US) (11.394 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------