



**Catalog N°:**  
BGBL1/0

|                              |                         |
|------------------------------|-------------------------|
| <b>BURNDY Catalog Number</b> | BGBL1/0                 |
| <b>UPC Number</b>            | 781810124840            |
| <b>Description</b>           | 1/0-14 AL/CU LAY-IN LUG |
| <b>Status</b>                | Active                  |
| <b>Web Use</b>               |                         |
| BURNDY Product Line          |                         |
| <b>Dimensional</b>           |                         |
| Length (in)                  | 1.50                    |
| Height (in)                  | 1.17                    |
| Hex Size                     | Slot                    |
| Size (Hex) or Size (Bolt)    | 3/8                     |
| Thickness                    | 0.22                    |
| D - in                       | 0.80                    |
| Pad Width (in)               | 0.60                    |
| E - in                       | 0.60                    |
| N (in)                       | 0.3                     |
| Hole Size (in)               | 0.28                    |





| <b>General</b>                    |  |
|-----------------------------------|--|
| Product Description               | Aluminum Lay-in Lug, 1/0-14 AWG, 3/8" Stud, Tin Plated |
| <b>Conductor(s)</b>               |  |
| Aluminum Size (Range)             | 8 AWG-1/0 AWG  |
| Copper Solid Size (Range)         | 14 AWG-1/0 AWG   |
| Copper Stranded (Range)           | 14 AWG-1/0   |
| <b>Physical</b>                   |  |
| Installation Torque               | 50   |
| Type of Plating                   | Tin - Electro Plated                                   |
| Plated (Yes or No)                | Y  |
| Product Material                  | Aluminum   |
| <b>Approvals / Certifications</b> |  |
| Rated for Direct Burial           | N  |
| UL Listed                         | Y  |
| CSA Certified                     | Y  |
| ROHS Compatible                   | Compliant  |
| UL Recognized                     | N  |
| CULUS                             | N  |
| Industry Standards                | UL468A-468B  |

