

Product data sheet

Characteristics

H361AWAVW

Safety switch, heavy duty, fusible, 30A, 600 VAC/
VDC, 3 poles, 20 hp, NEMA 12K, appleton, view
window



Main

Product	Receptacle Switch
For Use With	Plug ACP3034BC Appleton Powertite
Current Rating	30 A
Enclosure Rating	NEMA 3R/12 galvanized steel
Horsepower Rating	5 hp 480 V AC 50...60 Hz 3 phases NEC 240.6 15 hp 480 V AC 50...60 Hz 3 phases NEC 430.52 7.5 hp 600 V AC 50...60 Hz 3 phases NEC 240.6 20 hp 600 V AC 50...60 Hz 3 phases NEC 430.52 5 hp 250 V DC NEC 240.6
Disconnect Type	Fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Phase	3 phases
Electrical Connection	Receptacle
Certifications	UL listed
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12...AWG 2 aluminum AWG 14...AWG 2 copper
Wire Configuration	Without neutral 4-wire

Complementary

Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Depth	7 in (177.80 mm)
Tightening torque	45 lbf.in (5.08 N.m) AWG 6) 40 lbf.in (4.52 N.m) AWG 8)

Packing Units

Package 1 Weight	12.00 lb(US) (5.443 kg)
------------------	-------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
PVC free	Yes