

9001SKR9P1RH13

Illuminated push button, Harmony 9001SK, plastic, mushroom 41mm, red, 30mm, 2 positions, push-pull, 110...120V, 1 C/O



Main

| | |
|---------------------------|--------------------------|
| Range of Product | Harmony 9001SK |
| Product or Component Type | Illuminated push-button |
| Device short name | 9001SK |
| Type of operator | push-pull |
| Operator profile | Red mushroom Ø 41 mm |
| Light block supply | Via integral transformer |

Complementary

| | |
|--|--|
| Bezel material | Plastic |
| Mounting diameter | 1.18 in (30 mm) |
| Net Weight | 0.50 lb(US) (0.226 kg) |
| Operating position | Any position |
| Shape of signaling unit head | Round |
| Operator position information | 2 positions |
| Contacts type and composition | 1 C/O |
| Mechanical durability | 5000000 cycles |
| Connections - terminals | Screw clamp terminals, 1 x 0.22...2 x 1.5 mm ² IEC 60947-1 |
| Tightening torque | 7.08 lbf.in (0.8 N.m) IEC 60947-1 |
| Shape of screw head | Cross slotted |
| Contacts material | Silver alloy contacts |
| Short-circuit protection | 10 A cartridge fuse IEC 60947-5-1 |
| [I _{th}] conventional free air thermal current | 10 A |
| [U _i] rated insulation voltage | 250 V 3)IEC 60947-1 |
| [U _{imp}] rated impulse withstand voltage | 2.5 kV IEC 60947-1 |
| [I _{cm}] rated short-circuit making capacity | 12 KA 600 V AC-15, 7200 VA 15 KA 480 V AC-15, 7200 VA 30 KA 240 V AC-15, 7200 VA 60 KA 120 V AC-15, 7200 VA 0.1 KA 600 V DC-13 0.27 KA 250 V DC-13 0.55 KA 125 V DC-13 |
| Rated breaking capacity | 1.2 KA 600 V AC-15, 720 VA 1.5 KA 480 V AC-15, 720 VA 3 KA 240 V AC-15, 720 VA 6 KA 120 V AC-15, 720 VA 0.1 KA 600 V DC-13 0.27 KA 250 V DC-13 0.55 KA 125 V DC-13 |
| Light source | incandescent |
| Bulb base | BA 9s |
| [U _s] rated supply voltage | 110...120 V AC 50...60 Hz |
| Operator additional information | Screw-on plastic |
| Device presentation | Complete product |
| Cap/operator or lens colour | Red |

| | |
|---------------------------|--------------------------|
| [Us] rated supply voltage | 110...120 V |
| Light block supply | Via integral transformer |
| Operator profile | Mushroom Ø 41 mm |
| Type of operator | Push-pull |
| Supply frequency | 50...60 Hz |
| Size | 30 mm |
| Light source | Incandescent bulb |

Environment

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Electrical shock protection class | Class II IEC 60536 |
| IP degree of protection | IP66 IEC 60529 IP66 NF C 20-010 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 NEMA 4X |
| Standards | UL 508 EN/IEC 60947-5-1 JIS C 4520 CSA C22.2 No 14 JIS C 852 IEC 60947-1 IEC 60947-5-4 |
| Vibration resistance | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |



Ordering and shipping details

| | |
|-------------------|-------------------|
| Category | 21429-9001 SK,SKY |
| Discount Schedule | CS1 |
| GTIN | 785901043102 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.40 in (6.096 cm) |
| Package 1 Width | 4.50 in (11.43 cm) |
| Package 1 Length | 2.00 in (5.08 cm) |
| Package 1 Weight | 7.52 oz (213.188 g) |

Offer Sustainability

| | |
|---------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Toxic heavy metal free | Yes |

| | |
|-----------------------------|--|
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Contractual warranty | |
| Warranty | 18 months |