

Main

| | |
|---------------------------------------|--|
| Range of product | Telemecanique Safety light curtains XUSL |
| Accessory / separate part category | Mounting and fixing accessories |
| Accessory / separate part type | Fixing column |
| Offer type | Without mirror |
| Product compatibility | XUSL.E...16 to XUSL.E...61 with 2 beams |
| Accessory / separate part destination | Safety light curtain type 2 Safety light curtain type 4 |

Complementary

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -22...131 °F (-30...55 °C) -22...131 °F (-30...55 °C) |
| Ambient air temperature for storage | -22...158 °F (-30...70 °C) -22...158 °F (-30...70 °C) |
| Column height | 39.37 in (1000 mm) |
| Height protected | 24.02 in (610 mm) |
| Net weight | 7.72 lb(US) (3.5 kg) |

Packing Units


| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 10.90 lb(US) (4.945 kg) |
| Package 1 Height | 4.72 in (12 cm) |
| Package 1 width | 5.71 in (14.5 cm) |
| Package 1 Length | 43.70 in (111 cm) |

Offer Sustainability


| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Dimensions

With XUSZFB2



With XUSZFB1



Mounting and Clearance

