

BMH0702T01F2A

servo motor BMH, Lexium 32, 2.5Nm,
8000rpm, untapped shaft, with brake, IP54,
128bit encoder



Main

| | |
|---------------------------|---|
| Product or Component Type | Servo motor |
| Device short name | BMH |
| Maximum mechanical speed | 8000 rpm |
| Continuous stall torque | 22.13 Lbf.In (2.5 N.m) LXM32.D30M2 10 A, 115 V, single phase 22.13 lbf.in (2.5 N.m) LXM32.D18M2 6 A, 230 V, single phase |
| Peak stall torque | 56.64 Lbf.In (6.4 N.m) LXM32.D30M2 10 A, 115 V, single phase 65.50 lbf.in (7.4 N.m) LXM32.D18M2 6 A, 230 V, single phase |
| Nominal output power | 600 W LXM32.D30M2 10 A, 115 V, single phase 900 W LXM32.D18M2 6 A, 230 V, single phase |
| Nominal torque | 20.36 Lbf.In (2.3 N.m) LXM32.D30M2 10 A, 115 V, single phase 18.59 lbf.in (2.1 N.m) LXM32.D18M2 6 A, 230 V, single phase |
| Nominal speed | 2500 rpm LXM32.D30M2 10 A, 115 V, single phase 4000 rpm LXM32.D18M2 6 A, 230 V, single phase |
| Product compatibility | LXM32.D30M2 115 V single phase LXM32.D18M2 230 V single phase |
| Shaft end | Smooth shaft |
| IP Degree of Protection | IP54 standard |
| Speed feedback resolution | 131072 points/turn |
| Holding brake | With |
| Mounting Support | International standard flange |
| Electrical Connection | Rotatable right-angled connectors |

Complementary

| | |
|---------------------------|--|
| Range Compatibility | Lexium 32 |
| [Us] rated supply voltage | 240 V |
| Phase | Three phase |
| Continuous stall current | 5.38 A |
| Continuous power | 1.51 W |
| Maximum current Irms | 15 A LXM32.D30M2 17.5 A LXM32.D18M2 |
| Maximum permanent current | 17.71 A |
| Second shaft | Without second shaft end |
| Shaft diameter | 0.43 in (11 mm) |
| Shaft length | 0.91 in (23 mm) |
| Feedback type | Single turn SinCos Hiperface |
| Holding torque | 26.55 lbf.in (3 N.m) holding brake |
| Motor flange size | 2.76 in (70 mm) |
| Number of motor stacks | 2 |
| Torque constant | 0.46 N.m/A 248 °F (120 °C) |
| Back emf constant | 29.6 V/krpm 248 °F (120 °C) |
| Number of motor poles | 10 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------------------------|--|
| Rotor inertia | 1.24 kg.cm ² |
| Stator resistance | 1.15 Ohm 68 °F (20 °C) |
| Stator inductance | 3.6 mH 68 °F (20 °C) |
| Stator electrical time constant | 3.1 ms 68 °F (20 °C) |
| Maximum radial force Fr | 710 N 1000 rpm 560 N 2000 rpm 490 N 3000 rpm 450 N 4000 rpm 410 N 5000 rpm 390 N 6000 rpm |
| Maximum axial force Fa | 0.2 x Fr |
| Brake pull-in power | 7 W |
| Type of cooling | Natural convection |
| Length | 7.60 in (193 mm) |
| Centring collar diameter | 2.36 in (60 mm) |
| Centring collar depth | 0.10 in (2.5 mm) |
| Number of mounting holes | 4 |
| Mounting holes diameter | 0.22 in (5.5 mm) |
| Circle diameter of the mounting holes | 3.23 in (82 mm) |
| Net Weight | 7.28 lb(US) (3.3 kg) |

Ordering and shipping details

| | |
|-------------------|------------------------|
| Category | 18282-LEXIUM 32 MOTORS |
| Discount Schedule | PC53 |
| GTIN | 3606485199955 |
| Returnability | No |
| Country of origin | DE |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.33 in (11.0 cm) |
| Package 1 Width | 7.87 in (20.0 cm) |
| Package 1 Length | 15.75 in (40.0 cm) |
| Package 1 Weight | 4.41 lb(US) (2.0 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Servo Motors Dimensions

Example with Straight Connectors



- a: Power supply for servo motor brake
- b: Power supply for servo motor encoder
- (1) Shaft end, keyed slot (optional)

Dimensions in mm

| Straight connectors | | Rotatable angled connectors | | c (without brake) | c (with brake) | c1 | c2 | c3 | h | h1 | Ø | Ø1 for screws |
|---------------------|------|-----------------------------|------|-------------------|----------------|----|----|-----|------|-------------------------------------|-------|---------------|
| b1 | b2 | b1 | b2 | | | | | | | | | |
| 39.5 | 25.5 | 39.5 | 39.5 | 154 | 193 | 23 | 18 | 2.5 | 4 h9 | 12.5 ⁺⁰ _{-0.13} | 11 k6 | M4 x 14 |


Dimensions in in.

| Straight connectors | | Rotatable angled connectors | | c (without brake) | c (with brake) | c1 | c2 | c3 | h | h1 | Ø | Ø1 for screws |
|---------------------|----|-----------------------------|------|-------------------|----------------|------|------|------|---------|---------------------------------------|---------|---------------|
| b1 | b2 | b1 | b2 | | | | | | | | | |
| 1.55 | 1 | 1.55 | 1.55 | 6.06 | 7.59 | 0.90 | 0.70 | 0.09 | 0.16 h9 | 0.49 ⁺⁰ _{-0.0051} | 0.43 k6 | M4 x 0.55 |

115 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D30M2 servo drive




- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque

230 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D18M2 servo drive



- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque