

# XVC6B5

Harmony XVC, Monolithic precabled tower light, plastic, red orange green blue clear, Ø60, tube mounting, steady, IP23, 24 V AC/DC



## Main

|                                    |  |
|------------------------------------|--|
| Range of Product                   | Harmony XVC6   |
| Product or Component Type          | Complete pre-wired monolithic tower light  |
| Beacon or indicator bank unit type | 5 illuminated units  |
| Sound signalling                   | Without  |
| Mounting diameter                  | 2.36 in (60 mm)  |
| Component name                     | XVC  |
| Light source                       | LED steady red<br>LED steady orange<br>LED steady green<br>LED steady blue<br>LED steady clear |
| [Us] rated supply voltage          | 24 V   |
| Supply circuit type                | AC/DC  |

## Complementary

|  |   |
|--|---|
| Material                               | Polycarbonate: illuminated unit<br>ABS (acrylonitrile butadiene-styrene): base unit<br>PBT + ABS (UL94HB): top cover<br>STK (chromium-plated): support tube |
| Product mounting                       | On support tube, 22 mm  |
| Cable cross section                    | 0.00 in <sup>2</sup> (0.33 mm <sup>2</sup> )  |
| AWG Gauge                              | AWG 22  |
| Cable length                           | 23.62 in (600 mm)   |
| Marking                                | CE  |
| [Uimp] rated impulse withstand voltage | 0.8 kV  |
| Current Consumption                    | 125 mA  |
| Flashing frequency                     | 1 Hz  |
| Net Weight                             | 1.90 lb(US) (0.86 kg)   |
| Height                                 | 23.16 in (588.3 mm)   |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 61000-6-2<br>IEC 61000-6-3<br>IEC 61000-6-4 |
| Product Certifications                | UL  |
| Protective treatment                  | TC  |
| Ambient Air Temperature for Storage   | -31...158 °F (-35...70 °C)                      |
| Ambient Air Temperature for Operation | 14...122 °F (-10...50 °C)                       |
| Electrical shock protection class     | Class I IEC 61140                               |
| IP degree of protection               | IP23 vertical surface installation IEC 60529    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 22617-XVC TOWER LIGHTS |
| Discount Schedule | XV                     |
| GTIN              | 3606480032585          |
| Returnability     | No                     |
| Country of origin | ID                     |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 3.27 in (8.300 cm)       |
| Package 1 Width              | 3.27 in (8.300 cm)       |
| Package 1 Length             | 30.91 in (78.500 cm)     |
| Package 1 Weight             | 2.54 lb(US) (1.152 kg)   |
| Unit Type of Package 2       | P06                      |
| Number of Units in Package 2 | 10                       |
| Package 2 Height             | 29.53 in (75.000 cm)     |
| Package 2 Width              | 23.62 in (60.000 cm)     |
| Package 2 Length             | 31.50 in (80.000 cm)     |
| Package 2 Weight             | 44.14 lb(US) (20.020 kg) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



---

Pre-assembled and Pre-wired Tower Light

---

Support Tube Mounting

