

## KEYWERKS™ FACEPLATES WITH ID WINDOWS

---

PDS-0052



### DESCRIPTION

KEYWERKS™ Faceplates with Identification Windows are compatible with all KEYWERKS Keystone jacks, KEYWERKS connectors, and any other connectors with a standard Keystone footprint. Top and bottom identification windows allow for clear and quick port identification. All KEYWERKS Faceplates offer the flexibility to be installed on a standard electric box or directly onto the wall.

### FEATURES and BENEFITS

- Compatible with all KEYWERKS Keystone jacks, KEYWERKS connectors, and any other connector with a standard Keystone footprint
- Single gang available in 1, 2, 3, 4 and 6 ports version
- Double gang available in 6 and 12 ports version
- KEYWERKS Keystone jacks and KEYWERKS connectors can be independently installed/uninstalled
- Available in white and almond. Custom colors available on request
- Identification windows with write-on label and 6-32 Phillips screws included

**APPLICATIONS**

- Telecommunications room
- Equipment room
- Work area
- Multimedia applications

**ORDERING INFORMATION**

Part Number	Colour	Description	
WW000400	White	KEYWERKS ID faceplate, 1-port,	Single Gang
WW000401		KEYWERKS ID faceplate, 2-ports,	
WW000402		KEYWERKS ID faceplate, 3-ports,	
WW000403		KEYWERKS ID faceplate, 4-ports,	
WW000404		KEYWERKS ID faceplate, 6-ports,	
WW000410	Almond	KEYWERKS ID faceplate, 1-port,	
WW000411		KEYWERKS ID faceplate, 2-ports,	
WW000412		KEYWERKS ID faceplate, 3-ports,	
WW000413		KEYWERKS ID faceplate, 4-ports,	
WW000414		KEYWERKS ID faceplate, 6-ports,	
WW000405	White	KEYWERKS ID faceplate, 6-ports	Double Gang
WW000406		KEYWERKS ID faceplate, 12-ports	
WW000415	Almond	KEYWERKS ID faceplate, 6-ports	
WW000416		KEYWERKS ID faceplate, 12-ports	
Other colors available upon request.			

**INCLUDED**

Description
Clear plastic cover for ID window, white paper label, and 6-32 Phillips screws.

**PHYSICAL SPECIFICATIONS**

Parameter	Value
Plastic material faceplate	High impact UL 94V-0 ABS thermoplastic
Plastic material ID window	UL 94V-0 translucent plastic
Dimensions single gang faceplate	69.85 mm (2.75 in) x 115.06 mm (4.53 in)
Dimensions double gang faceplate	115.82 mm (4.56 in) x 115.06 mm (4.53 in)

**MECHANICAL SPECIFICATIONS**

Parameter	Value
Storage temperature	-40° C (-40° F) ~ 125° C (257° F)
Installation temperature	-20° C (-4° F) ~ 40° C (104° F)

**STANDARDS COMPLIANCE**

**RoHS**  
Directive on Restriction of Hazardous Substances.

**UL 94**  
Tests for Flammability of Plastic Materials for Parts in Devices and appliances.

**UL Listed**  
Communications-Circuit Accessories (Canada & USA).