COPPER WOUND, THREE PHASE

600 Delta Primary Volts 208Y/120 Secondary Volts 60 Hz

kVA	Catalog Number	Case Style	Approx. Dimensions (Inches) Width	Depth	Height	Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram
15	**SG3A0015PB0C**	DH1	21.5	20.1	22.0	210	F or W/C*	SCD 19
30	**SG3A0030PB0C**	DH2	25.8	23.8	28.8	340	F or W/C*	SCD 19
45	**SG3A0045PB0C**	DH2	25.8	23.8	28.8	400	F or W/C*	SCD 19
75	**SG3A0075PB0C**	DH3	28.3	27.0	36.0	590	F (Opt W/C)	SCD 19
112.5	**SG3A0112PB0C**	DH3	28.3	27.0	36.0	740	F (Opt W/C)	SCD 19
150	**SG3A0150PB0C**	DH4	31.5	29.5	44.5	930	F	SCD 19
225	**SG3A0225PB0C**	DH4	31.5	29.5	44.5	1350	F	SCD 19
300	**SG3A0300PB0C**	DH5	38.0	34.0	52.0	1800	F	SCD 19
500	**SG3A0500PB0C**	DH6	49.0	42.0	64.0	3200	F	SCD 20
750	**SG3A0750PB0C**	DH6	49.0	42.0	64.0	4050	F	SCD 20
1000	**SG3A1000PB0C**	DH7	54.0	47.0	72.0	5200	F	SCD 10

W/C: Built-in Wall Ceiling Mounting Opt W/C: Wall Ceiling Mounting Kit "DW3" Available OSHPD Certified for Floor Mounting Only

600 Delta Primary Volts 480Y/277 Secondary Volts 60 Hz

kVA	Catalog Number	Case Style	Approx. Dimensions (Inches) Width	Depth	Height	Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram
15	**SG3A0015PK0C**	DH1	21.5	20.1	22.0	210	F or W/C*	SCD 19
30	**SG3A0030PK0C**	DH2	25.8	23.8	28.8	340	F or W/C*	SCD 19
45	**SG3A0045PK0C**	DH2	25.8	23.8	28.8	400	F or W/C*	SCD 19
75	**SG3A0075PK0C**	DH3	28.3	27.0	36.0	590	F (Opt W/C)	SCD 19
112.5	**SG3A0112PK0C**	DH3	28.3	27.0	36.0	740	F (Opt W/C)	SCD 19
150	**SG3A0150PK0C**	DH4	31.5	29.5	44.5	930	F	SCD 19
225	**SG3A0225PK0C**	DH4	31.5	29.5	44.5	1350	F	SCD 19
300	**SG3A0300PK0C**	DH5	38.0	34.0	52.0	1800	F	SCD 19
500	**SG3A0500PK0C**	DH6	49.0	42.0	64.0	3200	F	SCD 20
750	**SG3A0750PK0C**	DH6	49.0	42.0	64.0	4050	F	SCD 20
1000	**SG3A1000PK0C**	DH7	54.0	47.0	72.0	5200	F	SCD 10

W/C: Built-in Wall Ceiling Mounting Opt W/C: Wall Ceiling Mounting Kit "DW3" Available OSHPD Certified for Floor Mounting Only