



Main

Range of product	Altivar
Range compatibility	Altivar 71
Product compatibility	ATV71HU30N4 ATV71HU30Y ATV71HU40N4 ATV71HU40Y ATV71HU55Y ATV71PU40N4Z ATV71WU40N4 ATV71HU15M3 ATV71HU22S6X ATV71HU30S6X ATV71HU40S6X ATV71HU55N4 ATV71HU55S6X ATV71HU75S6X ATV71PU55N4Z ATV71WU55N4 ATV71PU30N4Z ATV71WU30N4
Average power available	5.6 kW 122 °F (50 °C)
Ohmic value	60 Ohm

Complementary

Electrical connection	M10 bar wire
Protection type	Thermal protection via thermal overload relay
Net weight	46.30 lb(US) (21 kg)

Environment

Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-13...167 °F (-25...75 °C)
IP degree of protection	IP23

Packing Units

Package 1 Weight	13.23 lb(US) (6.000 kg)
------------------	-------------------------

Package 1 Height	4.550 dm
Package 1 width	7.400 dm
Package 1 Length	6.800 dm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------