

Product data sheet

Characteristics

8539SDA53V02S

NEMA Combination Starter, Type S, HHL electronic motor circuit protector, Size 2, 45A, 25HP at 600VAC, 3 phase, melting alloy, 120VAC coil, NEMA 12



Main

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non reversing
Number of Poles	3P
Horsepower Rating	10 Hp 230 V AC, 3 phase 25 Hp 575 V AC, 3 phase 7.5...10 Hp 200 V AC, 3 phase 20...25 hp 460 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	No indicator
Auxiliary Contacts	Without
Thermal overload type	Melting alloy 3
Disconnect Type	Mag-Gard circuit breaker

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
NEMA size	2

Ordering and shipping details

Category	21213-8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901519782
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.00 in (30.48 cm)
Package 1 Width	14.00 in (35.56 cm)
Package 1 Length	32.50 in (82.55 cm)
Package 1 Weight	87.84 lb(US) (39.845 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------