



## Main

Range	PowerLogic
Product name	CT
Product or Component Type	Current transformer
Secondary current	80 mA
Line Rated Current	400 A

## Complementary

Current transformer type	Standard for cable
Current transformer ratio	400 A/80 mA
[Ui] Rated Insulation Voltage	600 V
Depth	0.44 in (11.2 mm)
Diameter	Inner 0.98 in (25 mm) Outer 1.85 in (47.1 mm)
Net Weight	3.00 lb(US) (1.36 kg)
[Uimp] rated impulse withstand voltage	10 kV

## Environment

Product Certifications	CE
------------------------	----

## Ordering and shipping details

Category	09795-POWERLOGIC CURRENT TRANSFORMERS
Discount Schedule	PL1
GTIN	785901753988
Returnability	No
Country of origin	CA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.35 in (8.5 cm)
Package 1 Width	3.54 in (9.0 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	21.92 oz (621.422 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.