



### Main

Product or component type	Communication card
Range compatibility	Altivar 71 Altivar 71Q Altivar 61Q Altivar 61
Communication port protocol	Interbus
Connector type	9-way male SUB-D connector 9-way female SUB-D connector

### Complementary

Communication service	Communication monitoring I/O data Abort communication relationship Communication and drive status Identification of the card Initialize communication relationship Profile 21 Read object description Read parameter Write parameter
Supply	By drive but necessary to use an external supply if the inverter is not powered
Display type	1 LED BA (periodic data) 1 LED RC (bus input) 1 LED Rd (bus output) 1 LED TR (messaging) 1 LED U (power supply) Graphic display terminal control word received Graphic display terminal reference received
Net weight	0.66 lb(US) (0.3 kg)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10.23 oz (290 g)
Package 1 Height	2.83 in (7.2 cm)
Package 1 width	6.69 in (17 cm)

---

Package 1 Length	9.25 in (23.5 cm)
------------------	-------------------

---

**Offer Sustainability**

---

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
PVC free	Yes

---

**Contractual warranty**

---

Warranty	18 months
----------	-----------

---