

Main

Ampere Rating	10A
Application	Conveyor systems, packaging, textiles, transfer machines, presses, woodworking equipment, paint lines and test laboratories
Approvals	UL Listed File Number: E164353 CCN NKCR - CSA Certified File Number: LR44087 Class 3211 03 - CE Marked
Connection Type	(3) 0.5 Inch NPT
Contact Configuration	2 N.C.
Contact Operation	Slow Make - Slow Break
Contact Rating	A300 - Q300
Depth	1.57 Inches
Enclosure Rating	NEMA 1/4/12
Enclosure Type	Water tight and Dust tight (Indoor/Outdoor)
Features	Emergency Stop (latching)
Height	2.70 Inches
Maximum Voltage Rating	300V
Mounting Type	Surface
Reset Operator	Pushbutton
Terminal Type	Screw Clamp
Type	XY2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.