

Product data sheet

Specifications



PowerPacT multistandard - H-Frame - 100 A - 100 KA - Therm-Mag trip unit

NHJF36100TW

Main

Range of product	PowerPact multistandard
Range	PowerPact
Product name	H-Frame
Device short name	H-Frame
Product or component type	Circuit breaker
Device application	Distribution

Complementary

Poles description	3P
Control type	Toggle
Mounting mode	Unit mount
Mounting support	Backplate DIN rail Flush
Electrical connection	Terminal nut, line side Terminal nut, load side
[In] rated current	100 A 104 °F (40 °C)
[Ui] rated insulation voltage	750 V AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2
[Ue] rated operational voltage	525 V AC 50/60 Hz IEC 60947-2 690 V AC 50/60 Hz IEC 947-2 600 V AC 50/60 Hz UL 489
Breaking capacity code	HJ
Suitability for isolation	Yes
Utilisation category	Category A
Mechanical durability	4000 cycles
Electrical durability	4000 cycles
Connection pitch	1.8 in (45 mm)
Local signalling	ON/OFF indication
Contact position indicator	Yes
Trip unit name	TM
Trip unit technology	Thermal-magnetic
Trip unit protection functions	Basic protection
Trip unit rating	100 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Display type	3 LEDs
Breaking capacity	Icu 100 kA 220/240 V - AC IEC 947-2 Icu 65 kA 380/415 V - AC IEC 947-2 Icu 65 kA 440/480 V - AC IEC 947-2 Icu 25 kA 500/525 V - AC IEC 947-2 100 kA 240 V - AC UL 489 65 kA 480 V - AC UL 489 25 kA 600 V - AC UL 489
[Ics] rated service breaking capacity	Ics 100 kA 220/240 V - AC IEC 947-2 Ics 65 kA 380/415 V - AC IEC 947-2 Ics 65 kA 440/480 V - AC IEC 947-2 Ics 25 kA 500/525 V - AC IEC 947-2
Long time pick-up adjustment type Ir	Fixed
Long time pick-up adjustment range	1 In
Short-time pick-up adjustment type Isd	Fixed
[Isd] short-time pick-up adjustment range	1700 A
Overvoltage category	II
Provision for padlocking	Non padlockable
Height	6.4 in (163 mm)
Width	4.09 in (104 mm)
Depth	3.4 in (86 mm)
Standards	UL 489 W-C-375B/GEN CSA C22.2 No 5 NMX J-266 NEMA AB1 IEC 60947-2
Product certifications	CE CCC
Product weight	4.9 lb(US) (2.2 kg)
Tightening torque	44.3 lbf.in (5 N.m) 0.004...0.1 in² (2.5...95 mm²) AWG 14...AWG 3/0

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 IEC 60947-1 3 IEC 60664-1
Ambient air temperature for operation	104 °F (40 °C)
Ambient air temperature for storage	-58...185 °F (-50...85 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.118 in (13.000 cm)
Package 1 Width	7.244 in (18.400 cm)
Package 1 Length	8.425 in (21.400 cm)
Package 1 Weight	4.120 lb(US) (1.869 kg)
Unit Type of Package 2	S04

Number of Units in Package 2	6
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	26.411 lb(US) (11.980 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	291 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	10 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	278 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	F6740abd-d7a0-42b0-ba51-4931bf4d8226
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again




Repack and remanufacture

Recyclability potential, in %	45
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Offer Marketing Illustration

Product benefits / Features

PowerPacT H-Frame
Technical Features



Offer Marketing Illustration

Product benefits / Features

PowerPacT H-Frame
Molded Case Circuit Breakers



Scalable and sustainable
New breaker features enable scalable upgrades and are future-proof to meet environmental standards



Reliable quality
For proven installation, dependable performance and enhanced productivity



Innovative design
Improved access to information for troubleshooting and operations

Offer Marketing Illustration

Product benefits / Features



PowerPacT H-Frame
Range Accessories



Visi-Trip toggle



Phase barriers



Auxiliary switch



Mechanical lug



Shunt trip release



Lug shield

Offer Marketing Illustration

Product benefits / Features

PowerPacT H-Frame

Technical Benefits



- Available in 2-3 pole design.
- Available from 15-150A at up to 600VAC and 250VDC.
- Interrupting ratings (AIR) include:
 - D-18kA, G-35kA, J-65kA and L-100kA at 480VAC.
 - 20kA at 250VDC.
- Available with LED **Visi-Trip™** locator (optional), the first of its kind in the industry.
- Equipped with a unique snap-in terminal design that makes converting between busbar and lug options easy.
- Automatic molded case switches available at 150A.
- UL 489 Listed, CSA, NEMA, NMX, VDE, BS, CCC, IEC certified, and CE marked for global acceptance.